



Day Spa Steam Generator

SPECIFICATIONS

Input Voltage	208-240VAC Single Phase
Kilowatt Rating	12.0
Maximum Amperage	56 AMPS
Breaker Size	60 AMPS
Water Inlet	.3/8" Compression
Steam Outlet	.3/4" NPT
Drain Pan	.3/4" NPT
Safety Valve	.3/4" NPT
Electrical Connection	IEC 309
Maximum Room Size (cubic Feet)	250
Number of Rooms	2, 3 or 4
DS-2-250 = 2 Room, DS-3-250 = 3 Room, DS-4-250 = 4 Room	

Day Spa 250 Series Standard Equipment:

- Designed for Multiple steam room use, 2 to 4 Rooms.
- Includes Steam Distribution System Module to deliver steam to rooms independently. See separate Rough-in Guide.
- Designed for commercial use.
- Large capacity tank size.
- Unit has 208-240 volt power connections to be installed by your licensed electrician.
- Superior heating elements – low watt density.
- Includes Stainless Steel drip pan.
- Can be plumbed up to 50 ft. from the steam room without upsizing the generator.
- Stainless steel construction throughout.
- Split tank technology enhances performance and life-span.
- New style Polished Chrome Steam Head.
- Hardware Kit provided.
- Temp Sensor is built into controller.
- Optional Front Desk Sentinel Control is available & may be located up to 100' of cable run from the generator.

Installation Notes:

Generator must be installed by a licensed electrician.

Install this generator according to the installation guide supplied. Follow all local plumbing and electrical codes. Unit must be accessible for service and maintenance. Generator is factory sized: L x W x H = Steam Room Cubic Feet = 250 Cu. Ft. max. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

Product Specification Basics:

The steam generator unit dimensions are approximately 18-3/4" L x 13-3/4" W x 16" H in dimension. The generator shall be made from stainless steel and include: SmartSteam, PowerFlush and a Split Tank.

Shipping Information:

Weight	46 lbs.
Length	22 in.
Width	18 in.
Height	17 in.

For any further assistance please contact ThermaSol at
800.776.0711 or sales@thermasol.com

Visit www.thermasol.com for a complete product definition

