THERMATOUCH CONTROL

TT10V2-XX*

The ThermaTouch Control is a 10" LCD Touchscreen Control used to operate other ThermaSol modules such as Steam Room functions, Light, Sound and Tranquility Visualization, The control is approx. 10-3/4" Wide X 7-1/2" High X 3" Deep. It requires a wall cutout 10" Wide X 6-5/8" High and must have a clear in wall depth of 3-1/2".

SHIPPING WEIGHT

Weight | 12 lbs.

Length | 13 in.

Width | 12 in.

Height | 9 in.

FINISH CHART

PC | Polished Chrome

SC | Satin Chrome

PB | Polished Brass

SB | Satin Brass

AB | Antique Brass

COP | Polished Copper

ACOP | Antique Copper

ORB | Oil Rubbed Bronze

PN | Polished Nickel

SN | Satin Nickel

MB | Matte Black

AN | Antique Nickel

BN | Black Nickel

PG | Polished Gold

WHT | White

∗ Replace -XX with the desired finish in the above finish chart.

FEATURES

- Choose and download from a menu of popular Apps; shows, news, weather, video content, music and more

- Fully waterproof, ThermaTouch Plus can be installed anywhere: a shower, bathing area, patio, etc.

- Built-in Bluetooth® when paired with hydrovive

- Ethernet connection

- WiFi-enabled capabilities ensure that users automatically receive any updates to the software right to the controller, in-home after purchase.

- Powered by Android™

- Stereo audio output

- Alexa compatible

- Date and Time display

- Set steam time and temperature

- Set and control preferences for two users

- Operates: steam, digital shower, HydroVive light, sound and rain head.

SPECIFICATIONS

Construction | 6061 Aluminum bezel

Controllability | Steam, Light & Sound, digital shower valve.

Audio Out | 3.5mm jack connections

Power Supply | ThermaSol PDM (included)

Display | 10" Wide LCD Touch Screen

INSTALLATION NOTES

- Refer to ThermaSol installation Instructions Doc No. 81300 for complete instructions.

- Requires wall cut out opening of 10" Wide X 6.625" High X 3.5" Deep.

- Ensure 3-1/2" clearance around all sides of the mud ring cutout for controller clearance from walls or fixtures

- Use Mud Ring for Tile installation and ThermaTouch Control placement (04-8567).

- Ensure 3-1/2" clearance behind the rear of the control for cable clearance.

- The control should be installed 60 inches from the floor and as far from the steam outlet as possible.