



### SPECIFICATIONS – MicroTouch Control

Construction..... 6061 Billet Aluminum  
Display..... 16 LED Temperature Display  
Interface..... 3 Capacitive Touch Buttons  
Communication..... ThermaSol CAN Bus  
Supply Voltage..... 5V DC

Round Styling

#### **Basic Functions:**

- Recall last steam settings
- Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

#### **Installation Notes:**

**The control should be installed 60" inches from the floor of the shower, inside the shower only, and away from the steam head.**

#### **Finish Chart:**

Select desired finish and replace XXX with code.

PC = Polished Chrome	PN = Polished Nickel
SC = Satin Chrome	SN = Satin Nickel
PB = Polished Brass	BN = Black Nickel
SB = Satin Brass	AN = Antique Nickel
AB = Antique Brass	PG = Polished Gold
COP = Polished Copper	ORB = Oil Rubbed Bronze
ACOP = Antique Copper	
MB = Matte Black	WHT = White

#### **Product Specification:**

**The user interface control shall be 2.9" Dia x .63" in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.**

#### **Shipping Information:**

Weight..... 4 lbs.  
Length..... 12 in.  
Width..... 12 in.  
Height..... 6 in.

For any further assistance please contact  
ThermaSol at 800.776.0711 or  
[sales@thermasol.com](mailto:sales@thermasol.com)

